

## SAFE WORK PRACTICES CERTIFICATION

The undersigned hereby assures and certifies with respect to the development at

---

(address/city/state)

Safe Work Practices (SWP) were utilized on all lead-hazard reduction activities. Safe Work Practices are all those listed at 24 CFR 35.1350, which includes:

\_\_\_\_\_ • Occupant Protections

*Initial*

- Occupants were not be permitted to enter the worksite during hazard reduction activities until after hazard reduction work had been completed and clearance was been achieved.
  - \_\_\_ Relocation was required. (Attach evidence that the temporary housing was free of lead hazards)
  - \_\_\_ Relocation was not required.
- The unit and the worksite was be secured against unauthorized entry, and occupants' belongings were protected from contamination by dust-lead hazards and debris during hazard reduction activities. Occupants' belongings in the containment area were relocated to a safe and secure area outside the containment area.

\_\_\_\_\_ • Worksite Preparation

*Initial*

- The worksite was contained to prevent the release of leaded dust, and paint chips from hazard reduction activities within the worksite until they were safely removed.
- Warning signs were posted at each entry to a room where hazard reduction activities were conducted when occupants were present; and at each main and secondary entryway to a building from which occupants had been relocated.

\_\_\_\_\_ • Prohibited Methods of Treatment

*Initial*

The following methods were not used on this job site:

- Open flame burning or torching
- Machine sanding or grinding without a high-efficiency particulate air (H EPA) local exhaust control.
- Abrasive blasting or sandblasting without HEPA local exhaust control.
- Heat guns operating above 1100 degrees Fahrenheit.
- Dry sanding or dry scraping, except dry scraping in conjunction with heat guns or within 1 ft. of electrical outlets, or when treating defective paint spots totaling no

more than 2 sq. ft. in any one interior room or space, or totaling no more than 20 sq. ft. on exterior surfaces.

- Paint stripping in a poorly ventilated space using a volatile stripper that is a hazardous substance in accordance with regulations of the Consumer Product Safety Commission, an/or a hazardous chemical in accordance with the Occupational Safety and Health Administration regulations, as applicable to the work.

\_\_\_\_\_  
*Initial* • Qualified Workers

All persons carrying out lead hazard reduction activities were either supervised by an EPA abatement supervisor or attended a HUD-approved worker training course in lead hazard awareness, self protections and safe work practices prior to commencement of work.

\_\_\_\_\_  
*Initial* • Work Site Cleaning

After hazard reduction activities had been completed, the worksite was cleaned using cleaning methods, products and devises that are successful in cleaning up dust-lead hazards, such as a HEPA vacuum or other method of equivalent efficacy, and lead-specific detergents or equivalent.

Dated by the Undersigned this \_\_\_\_ day of \_\_\_\_\_, 20\_\_.

\_\_\_\_\_  
*Organization*

By: \_\_\_\_\_

Print Name: \_\_\_\_\_

State of Kansas            )  
   ) ss:  
 County of                    )

Subscribed and sworn to before me on this \_\_\_\_\_ day of \_\_\_\_\_, 20\_\_.

Notary Public

\_\_\_\_\_